

## Description

**Polypropylene 5948WZ** is an impact copolymer with a Melt Flow of 84 g/10min.

5948WZ is characterized by excellent stiffness and impact resistance, excellent antistatic properties, as well as extremely good flow properties to allow faster cycling through early demolding.

5948WZ complies with all applicable FDA regulations for food contact applications.

5948WZ has been developed for high-speed injection molding of thin-walled packaging containers and household articles.

## Characteristics

	Method	Unit	Typical Value
<b>Rheological Properties</b>			
Melt Flow	D-1238	g/10 min	84
<b>Mechanical Properties</b>			
Tensile Strength at Yield	D-638	psi (MPa)	3,600 (25)
Elongation at Yield	D-638	%	6
Flexural Modulus	D-790	psi (MPa)	170,000 (1,170)
Izod Impact Notched @ 23°C	D-256	ft.-lbs/in. (J/m)	2.0 (107)
<b>Thermal Properties<sup>(1)</sup></b>			
Melting Point	Total Method	°F (°C)	320-329 (160-165)
Unannealed Heat Deflection	D-648	°F (°C)	225 (107)
<b>Other Physical Properties</b>			
Density	D-1505	g/cm <sup>3</sup>	0.905

(1) Data developed under laboratory conditions and are not to be used as specification, maxima or minima.

5948WZ 101/2020



TOTAL PETROCHEMICALS & REFINING USA, INC.  
 POLYMERS AMERICAS  
[www.totalrefiningchemicals.com](http://www.totalrefiningchemicals.com)  
 1201 Louisiana Street  
 Suite 1800  
 Houston, TX 77002

TECHNICAL CENTER  
 P.O. Box 1200  
 Deer Park, Texas 77536  
 Phone: 281-884-7500

**1-800-344-3462**